

Protects Copiers, Mailing Systems, Large Format Printers and Other Office Equipment



The MOST Advanced Electronic Power Conditioner on the Market for HALF the Price and a QUARTER of the Weight of an Isolation Transformer



The Mega Conditioner is the new technology that will replace your isolation transformer and do the same job and with more features. The Mega Conditioner offers ultra power filtration and conditioning of normal and common mode noise which accounts for 90% of power-related problems. Voltage sags and swells can degrade your copier over time, the Mega Conditioner fixes them, effectively extending the life of your equipment.

Let's face it... copiers routinely have problems that cannot be solved by a power filter. In these cases, the Mega Conditioner will cut down on unforeseen and unexplainable issues and help copier dealers increase customer retention while reducing the burden on the service department.

Benefits:

- Solves problems not solved by power filters
- Increases profitability by reducing service calls
- Increases company credibility and customer retention
- Increases copies between calls
- Reduces error codes
- Reduces component degradation

If the Smart Power Systems equipment fails and this failure allows a surge to pass through and damage the connected equipment, Smart Power Systems will pay for the repair or replacement of the connected equipment up to \$25,000.






"No problem found" service calls could spell ruin for copier dealers. Left to account for hundreds of hours in downtime; failing to provide adequate equipment protection could damage customer loyalty and have a negative impact upon the business. With constant power conditioning, voltage regulation and TBF[™] technology, Mega Conditioners gives copier dealers a peace of mind.

Features:

- Ultra power conditioning
- Common Mode noise filtering: < 0.5 Volts</p>
- Normal Mode noise filtering: <10 Volts
- Voltage regulation
- Over and under voltage protection
- Site wiring fault indicator



1. Green LED: Normal Red LED: Reverse Polarity and No Ground

Disconnected Due to Over/Under Voltage

2. Buck

Boost
Voltage Meter

REAR



1. Network Protector (RJ45)

2. Output Receptacles

3. Circuit Breaker 4. Input Power Cord

MEGA1800 MEGA2400 MODEL Capacity (Amps) 15 20 Input Voltage Range / 50/60Hz 120V±21% Output Voltage Regulation 120 VAC±6% Over Voltage cutoff 140V TRANSIENT LET THROUGH VOLTAGE <0.5V Common Mode (N-G) TRANSIENT LET THROUGH VOLTAGE <10V Normal Mode (L-N) Input Plug 5-15P 5-20P Receptacles Two 5-15R Two 5-15/20R 13 x 5.5 x 6.6 (330 x 140 x 168) **Dimensions Inches** (mm) DxWxH Net Weight (Lbs./Kgs.) 14.7 / 6.7 16.5/7.5 Shipping Weight (Lbs./Kgs.) 16.2 / 7.4 18/8.2 Operating Environment 0-40°C at full load, 0-90% relative humidity (non condensing) WARRANTY 2 Years



1-800-882-8285

1760 Stebbins Dr. • Houston, TX 77043 • Tel.713-464-8000 Fax 713-984-0841 • Email sales@smartpowersystems.com • www.smartpowersystems.com Specifications subject to change without notice.

Specifications